

PLANARCAP® KPX DISPOSABLE CMP FILTERS

Filters for CMP slurry applications

Overview

Planarcap® KPX disposable CMP filters are ideally suited for filtration of CMP slurry in semiconductor fabrication applications. With an all-polypropylene (PP) construction and depth filter media, the Planarcap KPX filter features an optimized graded-density depth media pleated design to provide the best combination of surface area and media gradient.

Applications

- CMP slurry filtration
- Point-of-dispense (POD) and point-of-use (POU) filtration

Features and Benefits

- Optimized graded-density depth media pleated design providing best combination of surface area and media gradient
- Longer-lasting filtration performance
- Low pressure drop
- Optimized point-of-dispense and point-of-use filtration solution




Specifications

Materials:	Media, core, cage, shell	Polypropylene	
	Fitting connections	Inlet/outlet	¹ / ₄ " flare, ³ / ₈ " flare
		Vent/drain	1/8" MNPT, 1/4" flare
Dimensions:	Length	Short	152 mm (5.98")
		Long	208 mm (8.19")
	Diameter	68 mm (2.67")	
Maximum operating conditions:	Maximum operating pressure	0.27 MPa (2.7 bar, 40 psi) @ 25°C (77°F)	
	Maximum forward/reverse differential pressure	0.27 MPa (2.7 bar, 40 psi) @ 20°C (68°F)	
	Maximum operating temperature	40°C (104°F)	

Ordering Information

Planarcap KPX Disposable Filters



Performance Data


PC = Planarcap pleated depth

Flow Curve for Planarcap KPX (1/4" I/O Fitting) 9.00 8.00 7.00 6.00 9.00 1.0 µm 1.5 µm 1.5 µm 1.5 µm 1.5 µm

Flow Curve for Planarcap KPX (1/4" I/O Fitting) Using PSL Beads 100 90 1.0 µm 80 70 Retention (%) 60 50 40 30 20 10 0 8.0 1.0 1.2 0.2 0.4 0.6 1.4 1.6 Particle Size (µm)

Dimensions

Measured drawing (mm) available upon request.



For More Information

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit *www.entegris.com* and select the Customer Service link for the center nearest you.

Terms and Conditions of Sale

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, *visit www.entegris.com* and select the Legal Notices link from the footer.

Entegris®, the Entegris Rings Design®, Mykrolis® and Planarcap® are registered trademarks of Entegris, Inc.

ENTEGRIS, INC.

Corporate Headquarters | 129 Concord Road | Billerica, MA 01821 USA Customer Service Tel. +1 952 556 4181 | Customer Service Fax +1 952 556 8022 In North America 800 394 4083 | www.entegris.com

